



Lectores Láser POSline

SL2010

SL2020

SL2030

Manual de Programación



SET ALL DEFAULTS

Keyboard wedge,AT PS/2,UPC-A enable,UPC-E ENABLE EAN-8 enable,EAN-8 enable,EAN-13 enable,UPC-A enable with check Digital & System Character, UPC-E enable with check digital,

System character,code 128 enable,UCC/EAN-128 enable,code 39 Eanble but no check digit no transmit check digital,inter leaved 2 or 5 enable 14 digits,others are disable.

- Set the auto scan mode,with a needl into the switch hole and

Push the switch no or off.



BEEP AFTER GOOD DECODE



DO NOT BEEP AFTER GOOD DECODE



ENABLE UPC-E



DISABLE UPC-E



ENABLE UPC-A



DISABLE UPC-A



ENABLE EAN-8



DISABLE EAN-8



ENABLE EAN-13



DISABLE EAN-13



ENABLE BOOKLAND EAN



DISABLE BOOKLAND EAN



DECODE UPC/EAN WITH SUPPLEMENTALS



IGNORE UPC/EAN WITH SUPPLEMENTALS



AUTODISCRIMINATE UPC/EAN SUPPLEMENTALS



TRANSMIT UPC-A CHECK DIGIT



DO NOT TRANSMIT UPC-A CHECK DIGIT



TRANSMIT UPC-E CHECK DIGIT



DO NOT TRANSMIT UPC-E CHECK DIGIT

UPC-A Preamble



NO PREAMBLE
(<DATA>)



SYSTEM CHARACTER
(<SYSTEM CHARACTER> <DATA>)



SYSTEM CHARACTER & COUNTRY CODE
(< COUNTRY CODE> <SYSTEM CHARACTER> <DATA>)

UPC-E Preamble



NO PREAMBLE
(<DATA>)



SYSTEM CHARACTER
(<SYSTEM CHARACTER> <DATA>)



SYSTEM CHARACTER & COUNTRY CODE
(< COUNTRY CODE> <SYSTEM CHARACTER> <DATA>)



CONVERT UPC-E TO UPC-A
(ENABLE)



DO NOT CONVERT UPC-E TO UPC-A
(DISABLE)



ENABLE EAN ZERO EXTEND



DISABLE EAN ZERO EXTEND



TYPE IS EAN-13 (Default)



TYPE IS EAN-8



ENABLE CODE 128



DISABLE CODE 128



ENABLE UCC/EAN-128



DISABLE UCC/EAN-128



ENABLE CODE 39



DISABLE CODE 39



ENABLE CODE 39 CHECK DIGIT



DISABLE CODE 39 CHECK DIGIT



TRANSMIT CODE 39 CHECK DIGIT
(ENABLE)



DO NOT TRANSMIT CODE 39 CHECK DIGIT
(DISABLE)



ENABLE CODE 39 FULL ASCII



DISABLE CODE 39 FULL ASCII



BUFFER CODE 39
(ENABLE)



DO NOT BUFFER CODE 39
(DISABLE)



CLEAR BUFFER



TRANSMIT BUFFER



ENABLE CODE 93



DISABLE CODE 93



ENABLE INTERLEAVED 2 OF 5



DISABLE INTERLEAVED 2 OF 5



1 2 of 5 - ONE DISCRETE LENGTH



1 2 of 5 - TWO DISCRETE LENGTHS



CONVERT 1 2 of 5 to EAN-13
(ENABLE)



DO NOT CONVERT 1 2 of 5 to EAN-13
(DISABLE)



ENABLE DISCRETE 2 OF 5



DISABLE DISCRETE 2 OF 5



D 2 of 5 - ONE DISCRETE LENGTH



D 2 of 5 - TWO DISCRETE LENGTHS



ENABLE CODABAR



DISABLE CODABAR



ENABLE CLSI EDITING



DISABLE CLSI EDITING



ENABLE NOTIS EDITING



DISABLE NOTIS EDITING



ENABLE MSI PLESSEY



DISABLE MSI PLESSEY



ONE MSI Plessey CHECK DIGIT



TWO MSI Plessey CHECK DIGIT



TRANSMIT MSI Plessey CHECK DIGIT
(ENABLE)



DO NOT TRANSMIT MSI Plessey CHECK DIGIT
(DISABLE)



MOD 11/MOD 10



MOD 10/MOD 10



SCAN PREFIX



SCAN SUFFIX



SCAN SUFFIX 2



DATA AS IS



<DATA><SUFFIX 1>



<DATA> <SUFFIX 2>



<DATA <SUFFIX 1>><SUFFIX 2>



<PREFIX> <DATA>



<PREFIX><DATA><SUFFIX 1>



<PREFIX><DATA><SUFFIX 2>



<PREFIX><DATA><SUFFIX 1>><SUFFIX 2>



IBM PC/AT IBM PS/2-50, 55SX, 60, 70, 80 (Default)



IBM PS/2-30



IBM PC/XT



NCR 7052



North American (Default)



French



German



French International



Spanish



Italian



Swedish



British



ENABLE FAST TRANSMIT



DISABLE FAST TRANSMIT (Default)



INTERCHARACTER DELAY



0



1



2



3



4



5



6



7



8



9



CANCEL